



CUSHMAN

MODEL: Cushman Hauler 4x4
TYPE: GAS VEHICLE
MODEL YEAR: 2015
Part No: 639990G01



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: Subaru EH72 Fuel Injection 28 hp (20.8 kW) Rated, 43.9 ci (720 cc)

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fuel injection with electromagnetic fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge w/pre-filter

Electrical: Starter/Alternator, solid-state regulator, 12 Volt maintenance free battery (525 CCA, 60 minute reserve)

Drive Train Gas: Automatic, continuously variable transmission (CVT).

Brakes: 4-wheel hydraulic disc brakes. Hand operated park brake (floor mounted).

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Seating: Bench Seat

Cargo Bed: Roto-molded cross-linked polyethylene. Lifts for access to powertrain.

PRODUCT OVERVIEW

Dimensions

Overall Length 115.5 in (293.4 cm)

Overall Width 54.5 in (138.4 cm)

Overall Height 51 in (130 cm) top of steering wheel
76 in (193 cm) from canopy

Wheel Base 81.5 in (207 cm)

Front Wheel Track 43.38 in (110 cm)

Rear Wheel Track 44.38 in (113 cm)

Gnd Clearance @ Differential 7 in (17.8 cm) front skid plate

Cargo Box Width (inside) 44.0 in (112 cm)

Cargo Box Length (inside) 36.0 in (91 cm)

Cargo Box Depth (inside) 10.5 in (27 cm)

Cargo Box Capacity 9.6 cu ft (0.27 m³)

Cargo Box Material Roto-molded polyethylene

Vehicle Power

Power Source GAS: 4 cycle, 43.9 ci (720 cc)

Valve Train V Twin Cylinder OHV

Horsepower (kW) GAS 28 hp (20.8 kW) rated

Electrical System Starter/Alternator, solid-state regulator

Battery (Qty, Type) One 12 Volt maintenance free for starter/alt

Key or Pedal Start Key Start

Air Cleaner Dry cartridge w/ pre-filter

Lubrication Pressurized oil system

Oil Filter Spin-on oil filter

Cooling System Air cooled

Fuel Capacity 5.3 gallon (20 L) tank

Vehicle Power Cont.

Differential Rear Helical gears with rear diff lock
Front Auto Locking Differential

Gear Selection Manual Forward-Neutral-Reverse Lever

Rear Axle Ratio 14.38:1 Fwd; 14.36 Rev

Performance

Seating Capacity 2 Person

Curb Weight 1370 lb (621 kg)

Bed Load Capacity 800 lb (363 kg)

Vehicle load capacity 1200 lb (544 kg)

Outside Clearance Circle 33.2 ft (10.1 m)

Speed (Level Ground) 25 mph (40.1 kph)

Towing Capacity 1200 lb (544 kg)

Steering & Suspension

Steering Self-compensating rack and pinion

Front Suspension Independent MacPherson Strut

Rear Suspension Independent MacPherson Strut

Service Brake 4 wheel hydraulic disc brakes

Parking Brake Hand Operated

Front Tires Terra-Trac 25x10-12 K502

Rear Tires Terra-Trac 25x10-12 K502

Body & Chassis

Frame Welded steel with DuraShield™ powder coat

Front Body & Finish Injection Molded TPO

Rear Body & Finish Steel. Base coat/clear coat

Standard Color Black



CUSHMAN

OPTIONS & FIELD INSTALLED ACCESSORIES*

Item	Std	Opt	Fld
TIRES & WHEELS:			
All Terrain 25x10-12	X		
Mud Front 25x8-12, Rear 25x11-12		X	

Item	Std	Opt	Fld
COLORS:			
Body Color - Black	X		
Body Color - Patriot Blue		X	
Body Color - Bright White		X	
Body Color - Forest Green		X	
Body Color - Champagne Beige		X	
Custom Body Color		X	

Item	Std	Opt	Fld
SEAT OPTIONS:			
Seat Color - Black	X		
Headrests	X		

Item	Std	Opt	Fld
HAULING & TOWING:			
2 in (5 cm) Receiver	X		
Ball Hitch		X	
Angle Hitch		X	
Clevis Hitch		X	
Drop Ball Hitch		X	
Drop Angle Hitch		X	
Drop Clevis Hitch		X	
Winch Kit			X

Item	Std	Opt	Fld
WEATHER PROTECTION:			
Top Canopy (Not Available with Hard Cab)			X
Windshield Flat (Not Available with Hard Cab)			X
Windshield Fold Down (Not Available with Hard Cab)			X
Cab-Hard w/ Doors, Kick-out Windshield, Wiper & Washer			X
Cab-Soft			X
Rear Protective Screen (Not Available with Hard Cab)			X

Item	Std	Opt	Fld
STORAGE			
Left/Right Hand Glove Box Doors		X	

Item	Std	Opt	Fld
CARGO BEDS:			
Polyethylene Bed 9.6 cu ft	X		
Brushed Aluminum Bed 14.9 cu ft		X	
Black Aluminum Bed 10 cu ft		X	
No Bed		X	
Spray-In Bed Lining (Brushed Aluminum Bed)			X

Item	Std	Opt	Fld
ELECTRICAL:			
12 Volt Power Outlet	X		
Taillights	X		
Halogen Headlights	X		
Horn	X		
Brake Lights	X		
Reverse Buzzer	X		
LED Headlights		X	
Turn Signals (4-Way w/ Flashing Lights)		X	
Hour Meter		X	
Strobe Light			X
Working Lamp			X
Fog/Flood Lamp			X
Spark Arrestor			X

Item	Std	Opt	Fld
ROLL OVER PROTECTION SYSTEM (ROPS)			
ROPS			X

Item	Std	Opt	Fld
OTHER PERFORMANCE/ACCESSORIES:			
Grab Handle (Passenger)	X		
3 Point Seat Belts	X		
4 Cup Holders	X		
Brush Guard	X		
Key - Common	X		
Speed - High Speed: 25 MPH	X		
Fuel Guage	X		
Clutch Cover	X		
Grab Handle (Driver Side Optional)		X	
Premium Brush Guard		X	
Key - Unique		X	
Speed - Low Speed: 15 MPH		X	
Fire Extinguisher			X
Front CV Guard Kit - Stick Stopper			X
Skid Plate			X
Side Mirrors (Not Needed With Hard Cab)			X
Safety Kit			X
Durability Kit			X
Fuel Pack			X