



# SHUTTLE™ 2+2

MOVING PEOPLE, SAVING TIME.

The Cushman Shuttle 2+2 is the ideal choice for transporting personnel and visitors around a plant, resort, or the jobsite. Comfortably seating up to four passengers with generous bench seating, the rear seat will also convert to a cargo space. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp Kawasaki gas-powered engine, or 48-volt electric power drivetrain.

**LET'S WORK.®**

**13.5HP**  
GAS OR  
48V ELECTRIC

**14MPH**  
MAX  
SPEED

**800LB**  
LOAD  
CAPACITY



# CUSHMAN® SHUTTLE™ 2+2



**BRUSH GUARD  
AND HEADLIGHTS**



**CONVERTIBLE REAR SEAT  
TO CARGO AREA**

**BRAKE LIGHTS (OPTIONAL)**



**WINDSHIELD AND  
CANOPY (OPTIONAL)**

## OPTIONS & ACCESSORIES

- LED Headlights
- 4-Way Turn Signals
- Sun Canopy
- Windshield
- Weather Enclosure
- Hour Meter
- 12 Volt Outlet
- Strobe Light
- Locking Glove Box Door
- Rear Mirrors

| BODY & CHASSIS                    | ELECTRIC                                    | GAS                                       |
|-----------------------------------|---|---|
| <b>FRAME</b>                      | Welded steel with DuraShield™ powder coat   | Welded steel with DuraShield™ powder coat |
| <b>BODY &amp; FINISH</b>          | Injection Molded TPO                        | Injection Molded TPO                      |
| <b>STANDARD COLOR</b>             | Patriot Blue                                | Patriot Blue                              |
| <b>DIMENSIONS</b>                 |   |   |
| <b>OVERALL LENGTH</b>             | 108.5 in (276 cm)                           | 108.5 in (276 cm)                         |
| <b>OVERALL WIDTH</b>              | 48.5 in (123 cm)                            | 48.5 in (123 cm)                          |
| <b>OVERALL HEIGHT</b>             | 46.5 in (118 cm) (Top of steering wheel)    | 46.5 in (118 cm) (Top of steering wheel)  |
| <b>OVERALL HEIGHT (w/ CANOPY)</b> | 77.0 in (196cm) (Top of Sun Canopy)         | 77.0 in (196cm) (Top of Sun Canopy)       |
| <b>WHEEL BASE</b>                 | 65.5 in (166 cm)                            | 65.5 in (166 cm)                          |
| <b>FRONT WHEEL TRACK</b>          | 38.0 in (97 cm)                             | 38.0 in (97 cm)                           |
| <b>REAR WHEEL TRACK</b>           | 38.5 in (98 cm)                             | 38.5 in (98 cm)                           |
| <b>GROUND CLEARANCE</b>           | 4.5 in (11 cm)                              | 4.5 in (11 cm)                            |
| <b>LOAD DECK WIDTH</b>            | 40.0 in (102 cm)                            | 40.0 in (102 cm)                          |
| <b>LOAD DECK LENGTH</b>           | 32.0 in (81 cm)                             | 32.0 in (81 cm)                           |
| <b>POWER</b>                      |   |   |
| <b>POWER SOURCE</b>               | 48 Volts DC                                 | 4 Cycle 24.5 cu in (401 cc).              |
| <b>MOTOR TYPE</b>                 | Shunt Wound                                 | Single Cylinder OHV                       |
| <b>HORSEPOWER (KW)</b>            | 3.0 HP (2.2kW) Continuous                   | 13.5 hp (10.1 kW) Exceeds SAE J1940 Std.  |
| <b>ELECTRICAL SYSTEM</b>          | 48 Volt                                     | Starter/Generator. Solid State Regulator  |
| <b>BATTERY (QTY/TYPE)</b>         | Six, 8 Volt Deep Cycle                      | One, 12 Volt Maintenance Free             |
| <b>KEY OR PEDAL START</b>         | Pedal                                       | Pedal                                     |
| <b>AIR CLEANER</b>                | N/A   | Replaceable Dry Cartridge                 |
| <b>SPEED CONTROLLER</b>           | 250 Amp Solid State Controller              | N/A                                       |
| <b>OIL FILTER</b>                 | N/A   | Spin-On                                   |
| <b>COOLING SYSTEM</b>             | N/A   | Air Cooled                                |
| <b>FUEL CAPACITY</b>              | N/A   | 6.0 Gallon (22.7 L) tank                  |
| <b>DRIVE TRAIN</b>                | Motor Shaft Direct Drive                    | Continuously Variable Transmission (CVT)  |
| <b>TRANSAXLE</b>                  | Differential with Helical Gears             | Differential with Helical Gears           |
| <b>GEAR SELECTION</b>             | Dash Mounted Forward-Neutral-Reverse        | Dash Mounted Forward-Neutral-Reverse      |
| <b>REAR AXLE RATIO</b>            | 12.44:1                                     | 11.42:1 (Forward) 15.78:1 (Reverse)       |
| <b>PERFORMANCE</b>                |   |   |
| <b>SEATING CAPACITY</b>           | 4 Person                                    | 4 Person                                  |
| <b>CURB WEIGHT</b>                | 1036 lb (470kg)                             | 896 lb (406 kg)                           |
| <b>DRY WEIGHT</b>                 | 658 lb (298kg)                              | 861 lb (391 kg)                           |
| <b>DECK LOAD CAPACITY</b>         | 250 lb (113 kg)                             | 250 lb (113 kg)                           |
| <b>VEHICLE LOAD CAPACITY</b>      | 800 lb (363 kg)                             | 800 lb (363 kg)                           |
| <b>OUTSIDE CLEARANCE CIRCLE</b>   | 19 ft (5.8 m)                               | 19 ft (5.8 m)                             |
| <b>SPEED</b>                      | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)       | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)     |
| <b>STEERING &amp; SUSPENSION</b>  |   |   |
| <b>STEERING</b>                   | Self-compensating Rack and Pinion           |   |
| <b>FRONT/REAR SUSPENSION</b>      | Leaf Springs with Hydraulic Shock Absorbers |   |
| <b>SERVICE BRAKE</b>              | Rear Wheel Mechanical Self-adjusting Drum   |   |
| <b>PARKING BRAKE</b>              | Self-compensating, Single Point Engagement  |   |
| <b>FRONT/REAR TIRES</b>           | 18 x 8.50 - 8 (4-Ply Rated)                 |   |

**DEALER  
LOGO**

**[CUSTOMIZABLE DEALER NAME HERE]**

[Customizable Dealer Address]  
[Dealer City], [Dealer State], [Dealer ZIP], [Dealer Web Address]

[www.cushman.com](http://www.cushman.com)

800.241.5855 | ©2014 Textron Inc. All rights reserved.

60009-G1